



Xeikon 3030

Making Label Production Versatile

Stickler PP Silver AP901 Metalised Bopp

PHYSICAL CHARACTERISTICS

Stickler PP TC 50micron top coated silver polypropylene film produced with a brilliant gloss surface for crisp colour reproduction and optimum print results. Suitable for a number of print methods, from letterpress UV, screen, flexographic and offset printing. Stickler Silver PP can be used for a wide variety of applications where a demanding label substrate is required, from water, food & beverage, household, chemical and point of sale labels.

Facestock

Metallised silver – top coated polypropylene

Properties	Test Method	Result
Grammage	ISO 536	45 g/m ²
Caliper	ISO 534	50 microns

Adhesive

WG White Glassine

1 side siliconised supercalendered white glassine

Properties	Result
Grammage	62gsm
Caliper	55 microns

Laminate

Laminate shelf life	24 months stored at 20°C/50%RH
Typical laminate	130±6µm
Total weight	128±6

This technical specification includes our experience and know-how regards the following:

- a) The composition of our products
- b) Their generic adhesive qualities normalised by means of the ISO procedure and regarding the international rule Finat generally accepted in this sector.

Any reference to final use is subjected to our good knowledge and opinion and does not imply specific irrevocable guarantees for final use in end product labelling and packaging.

Over and above these standards the product user is responsible for assessing, testing and ensuring the specific scope of the label in certain applications by means of prior generic official approval.