



Xeikon 3030

Making Label Production Versatile

Super White Gloss RV20

PHYSICAL CHARACTERISTICS

Facestock

A super white and glossy surface, one side cast coated, mirror-finished printing paper. This paper has excellent wet strength, bulk and whiteness. Offers top print quality by letterpress, offset, flexo, screen in single or multi-color lines.

Basis weight ISO 536 : 80 gsm
Caliper ISO 534 : 88 µm

Adhesive

A general purpose emulsion acrylic removable adhesive with good initial tack and superior removability. It is compliant US FDA 21 CFR 175.105 (Adhesive) for food packaging & food processing as well as ECC 88/378/EEC, CEN EN71, PART 3.

Minimum Application Temperature : -12°C
Product Functional Service Temperature: -30°C / +80°C

Liner

A super-calendered blue glassine paper.

Basis weight ISO 536 : 62 gsm
Caliper ISO 534 : 56 µm

PERFORMANCE CHARACTERISTICS

Properties	Test Method	Typical values
Initial Tack on Glass	FINAT FTM9	5.0 N/25mm
Adhesion on Stainless Steel	FINAT FTM1	4.5 N/25mm (20mins)
Total Product Caliper	ISO 534	162 µm

Shelf life

1 year when stored at 22°C and 50% RH