

# Xeikon 3030

## Making Label Production Versatile

### Synlite ttr/rp77/hd70



#### Face SYNLITE

White, matt, PP-based film, clay-coated on one side.

#### Typical technical values

<b>Substance</b>	63	g/m <sup>2</sup>	ISO 536
<b>Caliper</b>	75	Microns	ISO 534
<b>Opacity</b>	85	%	DIN 53146/1

#### Printability

Flexography, screen, offset and letterpress.

#### Advantages:

Thin film for product labelling and for variable information labelling in logistics and industrial chemical end-uses. Good chemical resistance.

#### Adhesive RP77

Specially designed for labelling of HDPE drums and other rough substrates. Used with filmic face materials.

<b>Tack min</b>	15	N	FTM 9
<b>Shear min</b>	2	h	FTM 8
<b>Labelling temperature min</b>	0°C		
<b>Service temperature min</b>	-20°C		
<b>Service temperature max</b>	70°C		
<b>Total caliper</b>	149µm		

#### Backing HIGH DENSITY 70

White high transparent glassine backing paper. Specially developed for filmic label material giving the best conversion properties.

#### Typical technical values

<b>Substance</b>	64	g/m <sup>2</sup>	ISO 536
<b>Caliper</b>	56	microns	ISO 534
<b>Tensile strength MD</b>	7.5	KN/m	ISO 1924
<b>Tensile strength CD</b>	2.7	KN/m	ISO 1924

#### Shelf Life

From the date of manufacture: 2 years at +20 °C and RH 50%. Prolonged storage at higher temperatures and/or humidity levels will shorten the shelf life.

#### Environmental Statement

Synthetic labels applied to plastic packaging are typically fully recyclable together with the whole package.

For further information contact your local UPM Raflatac representative.

#### Information

PP film for product labelling and for variable information labelling in logistics and industrial chemical end-uses. Good chemical resistance and outdoor durability.

#### Disclaimer

Our recommendations are based on our most current knowledge and experience. As our products are used in conditions beyond our control, we cannot assume any liability for damage caused through their use. Users of our products are solely responsible that the product is suitable for its intended application, and have determined such at their sole discretion. Users must comply with any applicable legislation and/or testing requirements for the finished article, and are responsible for bringing their products to market. This publication does not constitute any warranty, express or implied, and is intended only for the recipient and cannot therefore be transferred to any third party. We cannot assume any liability for the use of our products in conjunction with other materials. All our products are sold subject to UPM Raflatac general sales conditions, and you should ensure that any existing laws are observed. This publication replaces all previous versions. All information is subject to change without notice.